

2 in 1

Paint & Alkali Sealer



*Ready Packaging 4 and 20 Kg-set

2 in 1

As primer and top coat

**Alkali
Resistant**

Without using alkali sealer

Economical

Excellent coverage

**Fast and
Practical**

Can be applied to damp Water walls

**Water
based**

Environmentally friendly

**Lotus
Effect**

Water does not easily penetrate

CEMENTO is specially formulated as a more effective and efficient wall/concrete coating. It can be applied without primer and alkali sealer and can be applied to substrates with high moisture levels (max 40%) for interior and exterior areas.

Application Recommendation :



1. Apartment / Housing complex.
2. Office Buildings.
3. School Buildings.
4. Shophouses.
5. Place of worship.
6. Residential house.

Application :

Stage	Product Name	Consumption	Coverage	Dry film thickness	Application tools
First Layer	Comp. A CEMENTO C7 (80 gr)+ Comp. B CEMENTO C7 (80 gr)+ Comp. C Water (40 gr) (A : B : C = 1 : 1 : 0.5)	0,2 kg-set	6-7 m ² /kg	±25 microns	Roll, brush
Second Layer	Comp. A CEMENTO C7 (80 gr)+ Comp. B CEMENTO C7 (80 gr)+ Comp. C Water (40 gr) (A : B : C = 1 : 1 : 0.5)	0,2 kg-set	6-7 m ² /kg	±25 microns	Roll, brush

Notes :

- The mixing Ratio between Component. A : Component B : Water is 1 : 1 : 0.5 (by weight).
- Add water into Component A, stir until evenly mixed, then gradually pour in component B while continuously stirring.
- Apply to the substrate 2 to 3 layers with an interval of at least 1 – 2 hours between each coat.



Standard Color Option :



White



Light Grey



Grey



Maize Yellow



Coral Red



Pastel Grey