

TECHNICAL DATA

- **Type** : Two components solvent free epoxy grout
- **Standard Color** : Tinting Color (more than 100 color choice)
- **Appearance** : Semi gloss
- **Solid content** : 98%
- **Coverage area m²/L-set** :

Ceramic thickness mm	Material Consumption (gr/m) Ceramic gap width			
	3 mm	5 mm	8 mm	10 mm
6	25.00	41.00	66.00	83.00
8	33.00	55.00	88.00	110.00
10	41.00	69.00	110.00	138.00
20	83.00	138.00	220.00	275.00

- **Drying time :**
 - Surface dry : 4 hours (30°C)
 - Hard dry : 24 hours (30°C)
 - Full Cure : 7 days (30°C)
- **Mixing Ratio** : Comp A : B = 9 : 1 by weight
- **Pot Life** : 30 minutes (30°C)
- **Application Temperature** : minimum 10°C

Available on standard color



www.propanraya.com Propan Raya ICC

@propanraya 08111 381 686

Brochure no.01/PET-11/OMP



EPOXY TILE GROUT PET-11




B01/PET-11/11052023/OMP

EPOXY TILE GROUT is a two components epoxy based tile grout that contain anti microbia (certificate 68/IPBCC/An.Mik/08/15) to prevent fungi and bacterial growth on grout permanently.

The advantage of using epoxy based ceramic grout is non-shrinkage during application, so it is suitable for new types of ceramics.

Another advantages are excellent adhesion and chemical resistance, so it is suitable for many area of application such as laboratory, hospital, pharmacy, restaurant, kitchen, factory, housing area, swimming pool, water storage tank as well as area where hygienic and sterile condition is required.




Ceramic tile



Granite tile



Marble



Natural Stone

ADVANTAGES

2 Component

Strong and durable

Strong Adhesion

Not shrinking & Anti cracking

Chemical Resistance

Easy to clean

Non Sagging

Can be applied vertically

Anti Bacteria

Clean and Hygiene


APPLICATION PROCEDURE

1. Clean ceramic and ceramic gap from dust and other dirt.
2. Mix component A and B (with mixing ratio A : B= 9 : 1), mix well. Do not add thinner or water.
3. Pour the mixture to substrate, flatten by using rubber trowel/paint knife. Make sure the gap are fully filled uniformly.
4. Clean off the surplus grout from ceramic surface by using damp sponge or clean wet clothes $\pm$ 5 minutes after application. Clean with water, use thinner only if necessary.
5. Let it dry for 20 - 24 hours.

AREA :



Swimming pool



Floor area or interior wall



Dry & wet area

NOTE:

- Please mix the solution as needed only because the pot-life after mixing is only 30 minutes.
- **Substrat :**
 - Ceramic
 - Paving block
 - Granite Stone
 - Natural Stone
 - Marble
- Tinting color available to match with ceramic color.