

HARDWAX OIL HWO-558

*Natural Look Protection
for Table, Wooden Floor &
Furniture Finishing*



propan
The Paint Specialist



Certificate ID03/0111



Certificate ID11/1102954057

www.propanraya.com [Propan Raya ICC](#)

[@propanraya](#) 08111 381 686



As we may know, solid wood (i.e Teak Wood & Sungkai Wood) cost are relatively quite expensive. In general, furniture owners of solid wood prefer best finishing with natural look.

Some of available wood finishing which are available in the market are melamine coating or polyurethane coating. Unfortunately, melamine coating has several disadvantages like the final look is not natural (looks like plastic), there will be white marks after put the hot or cold water glass. These can be happen, especially if the melamine coating is not correctly formulated.

Meanwhile for polyurethane coating, high skill of spray coating is required to provide excellent color appearance and smooth film.

Thus, Propan provide a solution to refinish wooden dining table with **Hardwax Oil**.

Why use Hardwax Oil?

1 Non Toxic

Safe for health

2 Natural Looks

Natural feel

3 Easy to Apply

Can be apply by brush

4 Easy Maintenance

Easy to refinish

5 Chemicals Resistance

Resistant to household chemicals


6 No Peeling

No chipping film


Hardwax Oil Application:



Wooden table



Wooden stairs



Wooden floor and wall

Application Procedure:

1. Mix well before used. To avoid uneven color, mixed different batches of cans (if any).
2. Use brush to apply Hardwax oil on the wooden surface. Let the oil penetrate, around 5-10 minutes.
3. Polish the wooden surface by polishing machine until there are no excess of oil and all surface fully coated.
4. Let dry for 4-5 hours. Repeat application process if there is some part of table are not coated.

Maintenance:

- For daily use, clean the surface with clean cloth/ rag.
- Re-apply 1 times Propan Hardwax Oil, if the coating has been thin,

Long Dining Table