



ULTRAN PARQUET LACK

Moisture Cured PU Parquet Floor Lacquer

**PROTECT AND BEAUTIFY
YOUR WOODEN FLOOR**



Application Tips UPL - 77E

1. Avoid to apply too thick layer of wood filler as it only serves to fill wood pores. Excessive application of wood filler will cause poor adhesion of paint.
2. Sanding gradually to get optimal result.
3. Avoid to apply thick coating on each layer, for optimal results apply thinner layer of paint repeatedly.
4. Make sure the previous layer is dry before recoating.
5. Make sure to use PROPAN Thinner Polyurethane for thinning and cleaning. Avoid using other types of thinner because it causes blushing, lower scratch resistance, hardness and leveling.
6. Component A, B and Thinner should be mixed properly and stir thoroughly.
7. Component B is sensitive towards moisture. Please close the cap tightly after use.
8. Apply in location/place with good ventilation.

ULTRAN AQUA PARQUET LACK

Waterbased Lacquer for Wooden Floor



Application Tips Ultran AQUA PARQUET LACK

1. Avoid to apply thick layer of wood filler as it only serves to fill wood pores. Excessive application of wood filler will cause poor adhesion of paint.
2. Sanding with sandpaper number 240 to get optimal result.
3. Avoid to apply thick coating on each layer, for optimal results apply thinner layer of paint repeatedly.
4. Make sure the previous layer is dry before recoating
5. Use clean water if necessary for dilution.

propan
The Paint Specialist



Certificate ID03/0111



Certificate ID11/1102954057



www.propanraya.com



Propan Raya ICC



@propanraya



08111 381 686

propan
The Paint Specialist

ULTRAN PARQUET SERIES

HIGH QUALITY
WOODEN FLOOR
COATINGS



ULTRAN PARQUET LACK


Moisture Cured PU Parquet Floor Lacquer

Ultran Parquet Lack UPL – 77 E is a moisture cured PU lacquer especially designed for finishing high quality wooden parquet flooring. It is durable and recommended for high traffic areas



ADVANTAGES

- Excellent abrasion and scratch resistance.
- Excellent transparency and clarity.
- Good leveling to provide smoother surface.
- Provide a layer of hard protection film and yet flexible enough to protect parquet.
- Excellent house-hold chemical resistance.



ULTRAN AQUA PARQUET LACK

Waterbased Lacquer for Wooden Floor

Ultran Aqua Parquet Lack APL-850 is an environmentally friendly water based lacquer to protect and beautify your wooden floor. Ultran Aqua Parquet Lack APL-850 is crystal clear, tough, odorless, easy to use and resistant to household chemical.



ADVANTAGES

- Can be easily applied with spray gun, roller or brush.
- Easy to re-finish and maintain.
- Non toxic
- Odorless
- Environmentally friendly



Application Procedure



ULTRAN PARQUET LACK

Moisture Cured PU Parquet Floor Lacquer

1. Sand along the wood grain with sandpaper number 180
2. Mix the components of UPL-77 E with mixture ratio as follows: A : B : Thinner = 1 : 1 : 1
3. Apply UPL – 77E by brush, rol or spray. Let it dry for 4-6 hours
4. Sand lightly along the wood grain with sandpaper number 400. Repeat step 2 and 3 twice to get optimum performance

ULTRAN AQUA PARQUET LACK

Waterbased Lacquer for Wooden Floor

1. Sand with sandpaper number 180 along the wood grain
2. Roll / brush / spray AQUA PARQUET LACK APL-850. Allows to dry for 3-4 hours
3. Sand lightly along the wood grain with sandpapaer number 400. Repeat step 2 twice to get optimal result

